



F1512

Technical Specifications

Frequency Range (+/-3 dB)	40 Hz - 21 kHz
Nominal Directivity (-6 dB) H x V	90° x 10°
Maximum Peak SPL (LF / MF / HF)	138 / 138 / 146 dB
Components LF	1 x 15in. Ferrite cone driver
Components MF	1 x 12in. Neodymium cone driver
Components HF	3 x 4in. Neodymium planar wave driver
Nominal Impedance LF	8 Ω
Nominal Impedance MF	8 Ω
Nominal Impedance HF	5.7 Ω
Power Handling (AES / Peak) LF	1.500 / 6000 W
Power Handling (AES / Peak) MF	650 / 2600 W
Power Handling (AES / Peak) HF	240 / 960 W
Rigging	Formula™ rigging system
Connections	2x SpeakON™ NL8
Enclosure Construction	18 / 24 mm Birch-ply
Finish	Black Polyurea PCP (Polyurea Cabinet Protection) finish
Protection Grille	Powder coated 2mm Metal Rigid Grille Acoustically transparent Foam for discrete appearance
Height Front (mm / in.)	445 / 17.52
Height Back (mm / in.)	320 / 12.59
Width Front (mm / in.)	900 / 35.43
Width Back (mm / in.)	900 / 35.43
Depth (mm / in.)	750 / 29.52
Weight (kg / lbs)	70 / 154.3
Supported Processing	Armonia Plus - Configurable Beam Steering setups