



F210

Technical Specifications

Frequency Range (+/-3 dB)	65 Hz - 21 kHz
Nominal Directivity (-6 dB) H x V	90° x 10°
Maximum Peak SPL (LF / MF / HF)	139 / 138 / 143 dB
Components LF	2 x 10in. Neodymium cone driver
Components MF	2 x 5in. Neodymium cone driver
Components HF	2 x 4in. Neodymium planar wave driver
Nominal Impedance LF	2 x 8
Nominal Impedance MF	6
Nominal Impedance HF	8
Power Handling (AES / Peak) LF	2 x 600 / 2 x 2.400 W
Power Handling (AES / Peak) MF	160 / 640 W
Power Handling (AES / Peak) HF	160 / 640 W
Rigging	Formula™ rigging system
Connections	2x SpeakON™ NL8
Enclosure Construction	18 / 24 mm Birch-ply
Finish	Black Polyurea PCP (Polyurea Cabinet Protection) finish
Protection Grille	Powder coated 2mm Metal Rigid Grille Acoustically transparent Foam for discrete appearance
Height Front (mm / in.)	328 / 12.91
Height Back (mm / in.)	247.5 / 09.74
Width Front (mm / in.)	924 / 36.37
Width Back (mm / in.)	924 / 36.37
Depth (mm / in.)	466 / 18.34
Weight (kg / lbs)	42 / 92
Supported Processing	Armonia Plus - Configurable Beam Steering setups