



## F215

### Technical Specifications

Frequency Range (+/-3 dB)	50 Hz - 21 kHz
Nominal Directivity (-6 dB) H x V	90° x 10°
Maximum Peak SPL (LF / MF / HF)	145 / 141 / 148 dB
Components LF	2 x 15in. Ferrite cone driver
Components MF	2 x 6.5in. Neodymium cone driver
Components HF	3 x 4in. Neodymium planar wave driver
Nominal Impedance LF	2 x 8
Nominal Impedance MF	8
Nominal Impedance HF	5.3
Power Handling (AES / Peak) LF	2 x 1.500 / 2 x 6.000 W
Power Handling (AES / Peak) MF	360 / 1.440 W
Power Handling (AES / Peak) HF	240 / 960 W
Rigging	Formula™ rigging system
Connections	2x SpeakON™ NL8
Enclosure Construction	18 / 24 mm Birch-ply
Finish	Black Polyurea PCP (Polyurea Cabinet Protection) finish
Protection Grille	Powder coated 2mm Metal Rigid Grille Acoustically transparent Foam for discrete appearance
Height Front (mm / in.)	450 / 17.71
Height Back (mm / in.)	350 / 13.78
Width Front (mm / in.)	1250 / 49.21
Width Back (mm / in.)	1250 / 49.21
Depth (mm / in.)	625 / 24.61
Weight (kg / lbs)	106 / 233.69
Supported Processing	Armonia Plus - Configurable Beam Steering setups