



## Gamma 8

### Technical Specifications

Frequency Range (+/-3 dB)	65 Hz - 20 kHz (60 Hz @ -10dB)
Nominal Directivity (-6 dB) H x V	70° x 70° - Conical
Maximum Peak SPL (LMF / MHF)	125 dB
Components LMF	1 x 8in. Neodymium cone driver
Components HF	1 x 1in. Neodymium compression driver
Nominal Impedance	8 (Internal passive network)
Power Handling (LMF / MHF)	250 / 1000 W
Rigging	3 x SpeakON™ NL4 (2 on rear side, 1 on bottom side)
Connections	12 mm Birch-ply
Enclosure Construction	Black PCP (Polyurea Cabinet Protection) finish
Finish	(Optional custom color, refer to the User Manual)
Protection Grille	Powder coated 1.5mm Metal Rigid Grille Acoustically Transparent Cloth for discrete appearance
Height Front (mm / in.)	400 / 15.74
Height Back (mm / in.)	400 / 15.74
Width Front (mm / in.)	270 / 10.62
Width Back (mm / in.)	78.5 / 03.09
Depth (mm / in.)	305 / 09.84
Weight (kg / lbs)	8 / 17.63
Supported Processing	Armonia Pro Audio Suite