



SM 15

Technical Specifications

Frequency Range (+/-3 dB)	50 Hz - 20 kHz
Nominal Directivity (-6 dB) H x V	60° x 60° Conical
Maximum Peak SPL (LMF / MHF)	134 / 136 dB
Components LMF	1 x 15in. Neodymium cone driver
Components MHF	1 x 1.4in. exit Neodymium compression driver
Nominal Impedance LMF	8 Ω
Nominal Impedance MHF	8 Ω
Power Handling (AES / Peak) LF	450 / 1800 W
Power Handling (AES / Peak) HF	110 / 440 W
Connections	2 x SpeakON™ NL4 - 2 x SpeakON™ NL4 Parallel Rear
Enclosure Construction	18 / 24 mm Birch-ply
Finish	Black Polyurea PCP (Polyurea Cabinet Protection) finish
Protection Grille	Powder coated 2mm Rigid Metal Grille
	Acoustically transparent Foam for discrete appearance
Height Front (mm / in.)	406 / 15.98
Height Back (mm / in.)	406 / 15.98
Width Front (mm / in.)	598 / 23.54
Width Back (mm / in.)	598 / 23.54
Depth (mm / in.)	593 / 23.34
Weight (kg / lbs)	28 / 61.72
Supported Processing	Armonia Pro Audio Suite