



Quadra 6

Technical Specifications

Frequency Range (+/-3 dB)	90 Hz - 22 kHz (75 Hz @ -10 dB)
Nominal Directivity (-6 dB) H x V	90° x 90° - Conical
Maximum Peak SPL	115 dB
Components LMF	1 x 6.5in. Neodymium cone driver
Components HF	1 x 0.7in. (0.55 Voice coil) Neodymium Tweeter (Coaxial)
Nominal Impedance	8 (Built - in passive network)
Power Handling (AES / Peak)	50 / 200 W
Connections	2 x Phoenix™ 4 Pole Connectors
Enclosure Construction	9 / 12 mm Birch-ply
Finish	Black Polyurea PCP (Polyurea Cabinet Protection) finish (Optional custom color, Refer to the User Manual)
Protection Grille	Powder coated 1.5mm Metal Rigid Grille Acoustically transparent Cloth for discrete appearance
Height Front (mm / in.)	220 / 08.66
Height Back (mm / in.)	220 / 08.66
Width Front (mm / in.)	220 / 08.66
Width Back (mm / in.)	220 / 08.66
Depth (mm / in.)	250 / 09.84
Weight (kg / lbs)	3.5 / 07.71
Supported Processing	Armonia Pro Audio Suite