



# 218R

## Technical Specifications

|                                |                                                                                               |
|--------------------------------|-----------------------------------------------------------------------------------------------|
| Frequency Range (+/-3 dB)      | 32 Hz - 150 Hz                                                                                |
| Nominal Directivity (-6 dB)    | Omnidirectional or cardioid (paired)                                                          |
| Maximum Peak SPL LF            | 144 dB                                                                                        |
| Components LF                  | 2 x 18in. Ferrite cone driver                                                                 |
| Nominal Impedance LF           | 2 x 8 Ω                                                                                       |
| Power Handling (AES / Peak) LF | 2 x 1.500 / 2 x 6.000 W                                                                       |
| Connections                    | 2 x SpeakON™ NL4                                                                              |
| Enclosure Construction         | 18 / 24 mm Ply Birch                                                                          |
| Finish                         | Black PCP (Polyurea Cabinet Protection) finish                                                |
| Protection Grille              | Powder coated 2mm Metal Rigid Grille<br>Acoustically transparent Foam for discrete appearance |
| Height Front (mm / in.)        | 1182,5 / 46.55                                                                                |
| Height Back (mm / in.)         | 1182,5 / 46.55                                                                                |
| Width Front (mm / in.)         | 575 / 22.63                                                                                   |
| Width Back (mm / in.)          | 575 / 22.63                                                                                   |
| Depth (mm / in.)               | 730 / 28.74                                                                                   |
| Weight (kg / lbs)              | 97,5 / 214,95                                                                                 |
| Supported processing           | Armonia Pro Audio Suite                                                                       |