



VH Full Range 15EV

Technical Specifications

| | |
|-----------------------------------|---|
| Frequency Range (+/-3 dB) | 65 Hz - 20 kHz |
| Nominal Directivity (-6 dB) H x V | 60° x 40° |
| Maximum Peak SPL (LF / MF / HF) | 139 / 141 / 136 dB |
| Components LF | 1 x 15in. Ferrite cone driver |
| Components MF | 2 x 6.5in. Neodymium cone driver |
| Components HF | 1 x 2in. exit Neodymium compression driver |
| Nominal Impedance LF | 8 |
| Nominal Impedance MF | 8 |
| Nominal Impedance HF | 8 |
| Power Handling (AES / Peak) LF | 1.500 / 6.000 W |
| Power Handling (AES / Peak) MF | 360 / 1.440 W |
| Power Handling (AES / Peak) HF | 110 / 440 W |
| Rigging | VH e-motion rigging™ system (optional touring version) |
| Connections | 2 x SpeakON™ NL8 - 1 x NL4 Sub/Bass out |
| Enclosure Construction | 18 / 24 mm Birch-ply |
| Finish | Black Polyurea PCP (Polyurea Cabinet Protection) finish |
| Protection Grille | Powder coated 2mm Rigid Metal Grille Acoustically transparent Foam for discrete appearance |
| Height Front (mm / in.) | 918 / 36.14 |
| Height Back (mm / in.) | 918 / 36.14 |
| Width Front (mm / in.) | 661 / 26.02 |
| Width Back (mm / in.) | 340 / 13.38 |
| Depth (mm / in.) | 639 / 25.15 |
| Weight (kg / lbs) | 67 / 147.70 |
| Supported Processing | Armonia Pro Audio Suite |