



VH Layer 112H & EMD

Technical Specifications

Frequency Range (+/-3 dB)	65 Hz - 21 kHz
Nominal Directivity (-6 dB) H x V	90° x 10°
Maximum Peak SPL (LF / MF / HF)	138 / 141 / 148 dB
Components LF	1 x 12in. Neodymium cone driver
Components MF	2 x 6.5in. Neodymium cone driver
Components HF	3 x 4in. Neodymium planar wave driver
Nominal Impedance LF	8
Nominal Impedance MF	8
Nominal Impedance HF	5.3
Power Handling (AES / Peak) LF	650 / 2.600 W
Power Handling (AES / Peak) MF	360 / 1.440 W
Power Handling (AES / Peak) HF	240 / 960 W
Rigging	Layer™ rigging system
Connections	2 x SpeakON™ NL8 - 1 x NL4 Sub/Bass out - 1 x NL4 EMD out
Enclosure Construction	out
Finish	18 / 24 mm Birch-ply
Protection Grille	Black Polyurea PCP (Polyurea Cabinet Protection) finish Powder coated 2mm Metal Rigid Grille
Height Front (mm / in.)	Acoustically transparent Foam for discrete appearance
Height Back (mm / in.)	450 / 17.71
Width Front (mm / in.)	360 / 14.17
Width Back (mm / in.)	545 / 21.45
Depth (mm / in.)	545 / 21.45
Weight (kg / lbs)	510 / 20.07
Supported Processing	45 + 8 / 99.20 + 17.6