



VH Layer 112H

Technical Specifications

| | |
|-----------------------------------|---|
| Frequency Range (+/-3 dB) | 65 Hz - 21 kHz |
| Nominal Directivity (-6 dB) H x V | 90° x 10° |
| Maximum Peak SPL (LF / MF / HF) | 138 / 141 / 148 dB |
| Components LF | 1 x 12in. Neodymium cone driver |
| Components MF | 2 x 6.5in. Neodymium cone driver (Additional) |
| Components HF | 3 x 4in. Neodymium planar wave driver |
| Nominal Impedance LF | 8 |
| Nominal Impedance MF | 8 (Optional) |
| Nominal Impedance HF | 5.3 |
| Power Handling (AES / Peak) LF | 650 / 2.600 W |
| Power Handling (AES / Peak) MF | 360 / 1.440 W (Additional) |
| Power Handling (AES / Peak) HF | 240 / 960 W |
| Rigging | Layer™ rigging system |
| Connections | 2 x SpeakON™ NL8 - 1 x NL4 Sub/Bass out - 1 x NL4 EMD out |
| Enclosure Construction | out |
| Finish | 18 / 24 mm Birch-ply |
| Protection Grille | Black Polyurea PCP (Polyurea Cabinet Protection) finish Powder coated 2mm Metal Rigid Grille |
| Height Front (mm / in.) | Acoustically transparent Foam for discrete appearance |
| Height Back (mm / in.) | 450 / 17.71 |
| Width Front (mm / in.) | 360 / 14.17 |
| Width Back (mm / in.) | 545 / 21.45 |
| Depth (mm / in.) | 545 / 21.45 |
| Weight (kg / lbs) | 510 / 20.07 |
| Supported Processing | 45 + 8 / 99.20 + 17.63 (Additional EMD) |